



SPECIFICATIONS

Rangehood Type	Undermount
GTIN	9351116002251
Country of Origin	Handcrafted in Italy
Designed to Suit	600-900mm GAS or INDUCTION
Controls	Touch Control
Speed Settings	4
Ducting Diameter	150mm
Recirculating	No
Extraction Type	Onboard Motor
Motor	Single Aluminium Motor
Extraction Rate	1020m3/h
Filter Type	10mm Stainless Steel Baffle
Noise Level	45dBA (min) to 63dBA (max)
Lighting	1 x 6W Dimmable And Dynamic Led Strip
Run-on Timer	10 Mins
Electrical Requirement	10A
Max Current (W)	286W
Product Dimensions (mm)	W850 x D290 x H445-730
Cut-Out Dimensions (mm)	W835 x D265
Weight	25kg
Warranty	3 Years (6 years when Sirius ducting is used)

KEY FEATURES



Single Motor

Power, performance and quiet efficiency are the most important elements in the performance of your Sirius hood. Sirius has worked tirelessly to create a product that ticks all the boxes.



10mm Stainless Steel Baffle Filters

Baffle filters feature interlocking baffles for effective grease removal, promoting smooth airflow. They're easy to maintain, offer superior filtration with a deep pleat design, and dishwasher safe.



Powerful Extraction

With an impressive maximum airflow of 1020M3/H, this rangehood quickly and effectively removes smoke, steam, heat, odours, and other airborne particles from the kitchen.



Induction Safe

This rangehood boasts efficient filters and extraction capabilities to effectively manage increased steam and moisture levels resulting from minimal ambient heat compared to gas cooking methods.



Extra Large Extraction Area

This rangehood has extra-large extraction area to ensure that even the largest pots and pans are taken care of, with maximum airflow coverage.



Hand Crafted in Italy

Sirius Rangehoods, a prestigious Italian brand founded in 1996, is renowned for its bold designs and commitment to premium materials and craftsmanship, making it a top choice for high-end rangehoods.

LINE DRAWING

